

General	▶ ET-703	▶ TD-2001	▶ TD-2002	▶ TD-4001	▶ TD-4002	▶ TD-4003
Short Description	High Frequency Driver	High Frequency Driver	High Frequency Driver	High Frequency Driver	High Frequency Compression Driver	High Frequency Driver
image						
Nominal Impedance	8 Ohm	8 Ohm	8 Ohm	16 Ohm	16 Ohm	16 Ohm
Frequency Range	5000-45000 Hz	500-22000 Hz	450-27000 Hz	600-20000 Hz	600-20000 Hz	600-20000 Hz
Rated Input Power	15 Watt	10 Watt	20 Watt	30 Watt	30 Watt	30 Watt
Maximum Input Power	30 Watt	30 Watt	40 Watt	60 Watt	60 Watt	60 Watt
Sound Pressure Level	107 dB/W (1m)	109 dB/W (1m)	111 dB/W (1m)	110 dB/W (1m)	110 dB/W (1m)	110 dB/W (1m)
Total Magnetic Flux	40.000 Mx	68.500 Mx	74.200 Mx	228.000 Mx	246.000 Mx	228.000 Mx
Magnetic Flux Density	20.000 G	18.000 G	19.500 G	20.000 G	21.500 G	20.000 G
Lowest Recommended Crossover	5.000 Hz	800 Hz	800 Hz	600 Hz	600 Hz	600 Hz
Voice Coil Diameter	35,0 mm	48,0 mm	48,0 mm	101,0 mm	101,0 mm	101,0 mm
Phasing Plug	3-slit type	3-slit type	3-slit type	5-slit type	5-slit type	5-slit type
Hole Size for Throat Connection		25,4 mm	25,4 mm	49,4 mm	50,8 mm	39,0 mm
Mounting Dimensions	2 screws: 25,4 / 4 screws: 98 mm	2 holes: 76,2 / 3 holes: 57,2 mm	3 holes: 57,2 / 4 holes: 76,2 mm	101.6 (4 Holes) mm	101 (4 Holes) mm	87,4 (4 Holes) mm
Weight	1,1 kg	6,4 kg	6,9 kg	13,5 kg	6,5 kg	9,9 kg
Dimensions (diameter x depth)	80 x 74 mm	141 x 107 mm	141 x 137 mm	178 x 156 mm	178 x 161 mm	171 x 156 mm